

## Service Bulletin

4000 Series 48 Issue 4

## Change to the recommended oils

January 2009

This service bulletin only applies to all 4000 series gas engines.

In line with Perkins continuous drive to improve product and quality, the following oils have been approved.

## Recommendations

Caution: Multigrade oils must not be used.

Engines that operate on natural gas should be lubricated by oils that have a nominal ash content of 0.5% by weight and a TBN (Total Base Number) between 5 and 7.

The following SAE40 monograde engine oils comply with the parameters given above:

- 1 Mobil Pegasus 705
- 2 Texaco/Caltex Geotex LA
- 3 Q8 Mahler MA
- 4 Castrol Duratec L
- 5 Mobil Pegasus 1005
- 6 Mobil Pegasus 805
- 7 BP Energas NGL
- 8 Shell Mysella LA
- 9 Shell Mysella XL
- 10 Total Nateria MH40
- 11 Chevron/Caltex (1) HDAX (0% and 0.5% sulphated ash)
- 12 Chevron HPLX low ash
- 13 Petro Canada Sentron LD 5000
- (1) This oil has a lower TBN value than the recommended minimum value, but the additive elements give the equivalent performance.

**Caution:** Oil change schedules for any of the above oils must be approved by Perkins Application Department, Stafford, England.

**Note:** Engines which run on land-fill gas should use the oils currently recommended in the relevant Users Handbook or Operation and Maintenance Manual. These oils have a higher ash content.

## End

Perkins Confidential Yellow. Issued by Perkins Engines Company Ltd, Peterborough PE1 5NA, England. © Proprietary information of Perkins Engines Company Ltd 2009, all rights reserved. The information is correct at the time of print. This bulletin is for technical information only and cannot be used as a basis for any claim including but not limited to warranty.

To enable the distribution lists for service bulletins to be maintained, If you currently receive service bulletins, but no longer require them, please contact Michael Lowrey by email at lowrey\_michael@perkins.com